

RTA15/RTR15 SERIES ROTARY TILLERS

HP REQUIRED
17-50 HP

HITCH
Cat. 1

TILLERS



Sized right for hobby farms and nurseries.


The 15 Series Land Pride Rotary Tiller is sized just right for compact tractors that are used on hobby farms and in nurseries in every corner of the country. The RTA15 operates in forward rotation while the RTR15 is reverse rotation. The sideshift feature on this series enables you to shift the tiller to the right to cover a tire track or get closer to obstacles, while allowing the driveline to remain straight.



Solid steel rotor shaft provides strength.



Sideshift gearbox slides with tiller. Sideshift capabilities allow right tire track to be covered.



Adjustable skid shoes control depth with various settings.

	RTA1558 RTR1558	RTA1566 RTR1566	RTA1574 RTR1574
Horsepower	17-50 HP		
Hitch	Cat. 1		
Width-Endplate to Endplate (cm)	58" (147)	66" (168)	74" (188)
Overall Width	64-1/4"	72-1/4"	80-1/4"
Weight - lb (kg)	444 (201)	476 (216)	508 (230)
Number of Flanges	7	8	9
No. of Blades per Flange	4 C-Shape		
Blade Spacing	7-7/8"		
Max. Tilling Depth[^]	6-1/2"		
Skid Shoe Settings	7		
Rotor Swing Diameter	15"		
Rotor Shaft Speed	211 rpm at 540 rpm PTO		
PTO Driveline	Category 3, Off-Center Shear Bolt or Slip Clutch		
Gearbox	50 HP, 540 rpm, Cast Iron Housing, Drain Plug		
Drive Chain	#80 High Tensile in Oil Bath		
Sprockets	Hardened Teeth, Splined Center		
Colors			

See page 47 for reverse-tilt diagram.

QUICK HITCH SYSTEM

5 YEAR
LIMITED GEARBOX
WARRANTY